

SHINGLE

DESIGNED TO GIVE AN AUTHENTIC SHINGLE EFFECT



Available for Icotherm Roofs:



GET IN TOUCH

01204 773 040 info@icotherm.co.uk

Units 8 & 9, Hurstwood Court, Mercer Way, Shadsworth Business Park, Blackburn, BB1 2QU



SHINGLE

DESIGNED TO GIVE AN AUTHENTIC SHINGLE EFFECT

ADVANTAGES

- British made
- Designed to give a traditional shingle appearance
- Lightweight
- Low pitch
- Good vandal resistance
- Quick installation
- Cost effective
- Virtually maintenance free
- Extensive range of accessories and flashings available
- Fully dry-fixed
- Guaranteed for 40 years against weather penetration
- Full technical support available
- Hidden fixing

TECHNICAL DATA

- Min. pitch: 15°
- Max. pitch: 90°
- Overall width: 1326mm
- Cover width: 1231mm
- Side lap: 95mm
- Step: 20mm
- Batten gauge (0.40mm): 250mm
- Roof cover per tile panel: 0.308m²
- Tile panels per m²: 3.2 No per m²
- Steel base: 0.40mm

Acrylic Top Coat
Stone Granules

Acrylic Base Coat

Epoxy Primer

- Weight as laid per m²: Under 7kg
- Fire resistance: AA classification equal to traditional roof tiles and slates

STOCK COLOURS:



NON-STOCK COLOURS:



Bramble Brown




Moss Green Tartan Green











- Manufactured using ISO 9001 approved materials
- ISO 14001